



TECHNICAL SHEET

CODE: FT-ID-01

VERSION: 1

DATE: 08/01/2021

CLEAN JOINTS

• OVERVIEW

The ceramic joint cleaner is a liquid mixture of acidic nature designed to remove dirt embedded in the joints of floors, ceramic walls, and bathroom and kitchen tiles, returning their original color without damaging the joints in a few minutes.

UN: 2031

IMO: N/A

1. ADVANTAGES AND PROPERTIES

High performance.

Ideal for removing dirt in ceramics.

Removes fats.

Phosphorus free.

2. MODES OF USE

Apply directly to the surface at a distance of approximately 20 cm and spray with a cloth, sponge or brush. Rinse with plenty of water.

3. COMPONENTS

Nitric acid, degreaser and water. It does not contain phosphorus.



TECHNICAL SHEET

CODE: FT-ID-01

VERSION: 1

DATE: 08/01/2021

4. PHYSICOCHEMICAL AND MICROBIOLOGICAL SPECIFICATIONS

Aspect	Translucent liquid
Color	Colourless
Smell	Characteristic
Density (g/cm³)	0.99 -1.21
pH (100% solution)	0 – 3

5. VARIETIES

Not applicable

6. PRESENTATIONS

Plastic container of 1L, 4L, 20 L

Mandatory health notification: NSOH10251-21CO

7. PRECAUTIONS AND WARNINGS

Respiratory protection: If necessary, use respiratory protection for vapors.



TECHNICAL SHEET

CODE: FT-ID-01

VERSION: 1

DATE: 08/01/2021

Hand protection: Wear protective gloves when handling this product.

Eye protection: Safety glasses should be worn, splash-proof of chemicals.

Keep out of reach of children. Do not swallow, avoid contact with eyes and mucous membranes. In case of ingestion take water. In case of contact with eyes, wash with plenty of water. Do not mix with alkaline substances. Do not mix with substances Wear gloves.

Do not use the product in joints made with silicones or acrylic putties, also on acid-sensitive surfaces such as marble, terrazzo, hydraulic mosaic floors, metal surfaces (aluminum, zinc, etc.), natural stone, carpets, wooden floors, satin glass, clothing.

It is recommended to perform a test before applying it as it can change the color of some ceramic joints

8. STORAGE CONDITIONS

Store in a cool, dry, ventilated place. Keep closed in its original container, away from sunlight and preferably from any other source of light and heat of long exposure.

9. MANUFACTURED

BYCSA SA. Barbosa (Plant): Corregimiento Popalito. Finca Los Búcaros km 8 Via a Porce. PHONE: (574)4682016

10. CONTACT US

Oficina principal en Medellín / PBX: 604 00 22
www.bycsa.co / mercadeo@bycsa.co / info@bycsa.co

Barbosa - Bogotá - Cali Barranquilla - Manizales
Ecuador Guayaquil PBX: (009 593 4) 265 82 21 - 82 22



TECHNICAL SHEET

CODE: FT-ID-01

VERSION: 1

DATE: 08/01/2021

Bogotá PBX: (571) 7427171
Medellín PBX: (574) 604 0022
Cali PBX: (572) 487 8080
Barranquilla PBX: (575) 385 2020
Manizales PBX: (576) 894 4100
Guayaquil (Ecu) PBX: (593) 422 90 329

1. CONTENT UPDATE

Date	Changes made	Responsible	Area
5/11/2021	Creating FT	Maria Fernanda Lopez	R+D

2. REVISION OF THE DOCUMENT

Date	Revised	Responsible	Area
5/11/2021	All content	Luis Miguel Caicedo	R+D

CONTROL OF THE DOCUMENTED INFORMATION

NUMBER	CODE	DATE	VERSION	DESCRIPTION
Technical	FT-ID-01	08/01/2021	1	Creating the document



TECHNICAL SHEET

CODE: FT-ID-01

VERSION: 1

DATE: 08/01/2021

PREPARED BY	REVIEWED BY	APPROVED BY
Luis Miguel Caicedo Jimenez	Luz Bibiana Sánchez Henao	Isabel Cristina López Arteaga